

TECHNICAL DATASHEET

SIPDU Series
Intelligent PDU with RS-485
12 Sockets DIN49440
Input Ceeform 16A



Input : Ceeform 16A



Output : (12) DIN49440



Cable : 3G*2.5mm²*3m



Max. Power : 4000 Watt

Specification		
Brand	YURRO	
Product Name	Power Distribution Unit	
Part Number	Y-A12-11-4	
Physical		
Case	Aluminium alloy coated Black	
Power Input	Top singel input	
Bracket Install	Vertical installation	
Product Size	L x W x H = 1028 x 50 x 60mm	
Mounting Length	989mm	
Mounting Style	2 ends Brakets	
Fittings	4 pcs cross screw (φ 6 x 16mm), 4pcs M6 float nut	
Output		
Socket Type	DIN49440 / Schuko	
Socket Unit	12 x DIN49440 / Schuko	
Max. Ouput Current	16A	
Input		
Cable with Plug	Ceeform 16A	
Cable Spesification	3G*2.5mm ² *3M	
Rating Voltage	220 - 250VAC 50 - 60 Hz	
Rating Current	16A	
Max. Current	16A	
Max. Power	4000 watt	
Protection Function		
3LSP	3Lights Surge Protector	
Feature		
SIPDU Meter	. RS-485 . Monitor input voltage . Monitor total load current . Monitor energy consumption	. Monitor power factor . Monitor output option . Voltage threshold setting . Current threshold setting
Add-In		
Interior Connection Wire	Brass bar	
Interior Connection Style	Soldering tin	
Fix the Cable	PG Cable clamp	
Safety Authentication	CE	
Warranty		
2 (two) Years	Repair or replace	