

TECHNICAL DATASHEET

New IPDU Series
Intelligent PDU with SNMP
12 Sockets DIN49440
Input Ceeform 32A



3L Surge Protector



Input : Ceeform 32A



Output : (12) DIN49440



Cable : 3G*4.0mm²*3m



Max. Power : 8000 Watt

Specification

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-A12-12-5

Physical

Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1028 x 50 x 60mm
Mounting Length	989mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut

Output

Socket Type	DIN49440 / Schuko
Socket Unit	12 x DIN49440 / Schuko
Max. Ouput Current	16A

Input

Cable with Plug	Ceeform 32A
Cable Spesification	3G*4.0mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	8000 watt

Protection Function

3LSP	3Lights Surge Protector
------	-------------------------

Feature

New IPDU Meter	. Remote network management	. Monitor energy consumption
	. Cascade management	. Monitor power factkor
	. RS485	. Monitor output options
	. SNMP V1, V2, V3	. Voltage threshold setting
	. Monitor input voltage	. Current threshold setting
	. Monitor total load current	. TH Sensor (optional)
	. Monitor total load power	. USB port

Add-In

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

Warranty

2 (two) Years	Repair or replace
-----------------	-------------------