


TECHNICAL DATASHEET

SIPDU Series
Intelligent PDU with RS-485
16 Sockets DIN49440
6 Input Ceeform 32A



3L Surge Protector



Input : Ceeform 32A



Output : (16) DIN49440



Cable : 3G*4.0mm²*3m



Max. Power : 8000 Watt

Specification	
Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-A16-11-5
Physical	
Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1328 x 50 x 60mm
Mounting Length	1289mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw (φ 6 x 16mm), 4pcs M6 float nut
Output	
Socket Type	DIN49440 / Schuko
Socket Unit	16 x DIN49440 / Schuko
Max. Ouput Current	16A
Input	
Cable with Plug	Ceeform 32A
Cable Spesification	3G*4.0mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	8000 watt
Protection Function	
3LSP	3Lights Surge Protector
Feature	
SIPDU Meter	<ul style="list-style-type: none"> . RS-485 . Monitor input voltage . Monitor total load current . Monitor energy consumption . Monitor power factor . Monitor output option . Voltage threshold setting . Current threshold setting
Add-In	
Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE
Warranty	
2 (two) Years	Repair or replace