

# TECHNICAL DATASHEET

PDU 16 Sockets DIN49440  
With 3L Surge Protector + AV6 Meter  
Input IEC C20, 16A



3L Surge Protector



Input : IEC C20, 16A



Output : (16) DIN49440



Cable : 3G\*2.5mm<sup>2</sup>\*3m



Max. Power : 4000 Watt

**Specification**

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-A16-6-3

**Physical**

Case	Aluminium alloy coated Black
Power Input	Bottom single input
Bracket Install	Vertical installation
Product Size	L x W x H = 1328 x 50 x 60mm
Mounting Length	1289mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw ( $\phi$ 6 x 16mm), 4pcs M6 float nut

**Output**

Socket Type	DIN49440 / Schuko
Socket Unit	16 x DIN49440 / Schuko
Max. Output Current	16A

**Input**

Cable with Plug	IEC C20, 16A
Cable Specification	3G*2.5mm <sup>2</sup> *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	16A
Max. Current	16A
Max. Power	4000 watt

**Protection Function**

3LSP	3Lights Surge Protector
------	-------------------------

**Control Function**

AV6	<ul style="list-style-type: none"> <li>. Monitor input voltage</li> <li>. Monitor power factor</li> <li>. Monitor frequency</li> <li>. Monitor total load power</li> </ul>	<ul style="list-style-type: none"> <li>. Monitor total load current</li> <li>. Monitor energy consumption</li> <li>. Button reset energy</li> </ul>
-----	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------

**Add-In**

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

**Warranty**

2 ( two ) Years	Repair or replace
-----------------	-------------------