

TECHNICAL DATASHEET

New IPDU Series
Intelligent PDU with SNMP
20 Sockets DIN49440
Input Schuko 16A



3L Surge Protector



Input : Schuko 16A



Output : (20) DIN49440



Cable : 3G*2.5mm²*3m



Max. Power : 4000 Watt

Specification

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-A20-12-1

Physical

Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1428 x 50 x 60mm
Mounting Length	1389mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut

Output

Socket Type	DIN49440 / Schuko
Socket Unit	20 x DIN49440 / Schuko
Max. Ouput Current	16A

Input

Cable with Plug	Schuko, 16A
Cable Spesification	3G*2.5mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	16A
Max. Current	16A
Max. Power	4000 watt

Protection Function

3LSP	3Lights Surge Protector
------	-------------------------

Feature

New IPDU Meter	. Remote network management . Cascadae management . RS485 . SNMP V1, V2, V3 . Monitor input voltage . Monitor total load current . Monitor total load power	. Monitor energy consumption . Monitor power factcor . Monitor output options . Voltage threshold setting . Current threshold setting . TH Sensor (optional) . USB port
----------------	---	---

Add-In

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

Warranty

2 (two) Years	Repair or replace
-----------------	-------------------