

# TECHNICAL DATASHEET

SIPDU Series  
Intelligent PDU with RS-485  
24 Sockets DIN49440  
Input IEC C14, 10A



● 3L Surge Protector



Input : IEC C14, 10A



Output : (24) DIN49440



Cable : 3G\*2.5mm<sup>2</sup>\*3m



Max. Power : 2500 Watt

**Specification**

<b>Brand</b>	<b>YURRO</b>
<b>Product Name</b>	<b>Power Distribution Unit</b>
<b>Part Number</b>	<b>Y-A24-11-2</b>

**Physical**

Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1578 x 50 x 60mm
Mounting Length	1539mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw ( φ 6 x 16mm), 4pcs M6 float nut

**Output**

Socket Type	DIN49440 / Schuko
Socket Unit	24 x DIN49440 / Schuko
Max. Ouput Current	16A

**Input**

Cable with Plug	IEC C14, 10A
Cable Spesification	3G*2.5mm <sup>2</sup> *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	10A
Max. Current	10A
Max. Power	2500 watt

**Protection Function**

3LSP	3Lights Surge Protector
------	-------------------------

**Feature**

SIPDU Meter	. RS-485	. Monitor power factor
	. Monitor input voltage	. Monitor output option
	. Monitor total load current	. Voltage threshold setting
	. Monitor energy consumption	. Current threshold setting

**Add-In**

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

**Warranty**

2 ( two ) Years	Repair or replace
-----------------	-------------------