

TECHNICAL DATASHEET

PDU 24 Sockets DIN49440
With 3L Surge Protector + AV6 Meter
Input IEC C20, 16A



3L Surge Protector



Input : IEC C20, 16A



Output : (24) DIN49440



Cable : 3G*2.5mm²*3m



Max. Power : 4000 Watt

Specification		
Brand	YURRO	
Product Name	Power Distribution Unit	
Part Number	Y-A24-6-3	
Physical		
Case	Aluminium alloy coated Black	
Power Input	Bottom singel input	
Bracket Install	Vertical installation	
Product Size	L x W x H = 1578 x 50 x 60mm	
Mounting Length	1539mm	
Mounting Style	2 ends Brakets	
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut	
Output		
Socket Type	DIN49440 / Schuko	
Socket Unit	24 x DIN49440 / Schuko	
Max. Ouput Current	16A	
Input		
Cable with Plug	IEC C20, 16A	
Cable Spesification	3G*2.5mm²*3M	
Rating Voltage	220 - 250VAC 50 - 60 Hz	
Rating Current	16A	
Max. Current	16A	
Max. Power	4000 watt	
Protection Function		
3LSP	3Lights Surge Protector	
Control Function		
AV6	. Monitor input voltage . Monitor power factor . Monitor frequency . Monitor total load power	. Monitor total load current . Monitor energy consumption . Button reset energy
Add-In		
Interior Connection Wire	Brass bar	
Interior Connection Style	Soldering tin	
Fix the Cable	PG Cable clamp	
Safety Authentication	CE	
Warranty		
2 (two) Years	Repair or replace	