

# TECHNICAL DATASHEET

14 Socket Mix. Socket  
Intelligent PDU with SNMP  
(12) IEC C13 + (2) IEC C19  
Input Ceeform 16A



Input : Ceeform 16A



Output : (12) IEC C13  
(2) IEC C19



Cable : 3G\*2.5mm<sup>2</sup>\*3m



Max. Power : 4000 Watt

**Specification**

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B12C2-12-4

**Physical**

Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 928 x 50 x 60mm
Mounting Length	889mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw ( φ 6 x 16mm), 4pcs M6 float nut

**Output**

Socket Type	IEC C13 and IEC C19
Socket Unit	(12)C13 + (2)C19

**Input**

Cable with Plug	Ceeform 16A
Cable Spesification	3G*2.5mm <sup>2</sup> *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	16A
Max. Current	16A
Max. Power	4000 watt

**Protection Function**

3LSP	3Lights Surge Protector
------	-------------------------

**Feature**

New IPDU Meter	. Remote network management	. Monitor energy consumption
	. Cascade management	. Monitor power factkor
	. RS485	. Monitor output options
	. SNMP V1, V2, V3	. Voltage threshold setting
	. Monitor input voltage	. Current threshold setting
	. Monitor total load current	. TH Sensor ( optional )
	. Monitor total load power	. USB port

**Add-In**

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

**Warranty**

2 ( two ) Years	Repair or replace
-----------------	-------------------