

TECHNICAL DATASHEET

**14 Holes PDU Mix. Socket
(12) IEC C13 + (2) IEC C19
with 3L Surge Protector + MCB
Input Schuko 16A**



3L Surge Protector



Input : Schuko 16A



Output : (12) IEC C13
(2) IEC C19



Cable : 3G*2.5mm²*3m



Max. Power : 4000 Watt

Specification

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B12C2-3-1

Physical

Case	Aluminium alloy coated Black
Power Input	Bottom single input
Bracket Install	Vertical installation
Product Size	L x W x H = 928 x 50 x 60mm
Mounting Length	889mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut

Output

Socket Type	IEC C13 and IEC C19
Socket Unit	(12)C13 + (2)C19

Input

Cable with Plug	Schuko, 16A
Cable Specification	3G*2.5mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	16A
Max. Current	16A
Max. Power	4000 watt

Protection Function

3LSP	3Lights Surge Protector
Circuit Breaker	1Pole 16A

Add-In

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

Warranty

2 (two) Years	Repair or replace
---------------	-------------------