

TECHNICAL DATASHEET

**14 Holes PDU Mix. Socket
(12) IEC C13 + (2) IEC C19
With 3L Surge Protector + AV6 Meter
Input Ceeform 16A**



3L Surge Protector



Input : Ceeform 16A



Output : (12) IEC C13
(2) IEC C19



Cable : 3G*2.5mm²*3m



Max. Power : 4000 Watt

Specification	
Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B12C2-6-4
Physical	
Case	Aluminium alloy coated Black
Power Input	Bottom single input
Bracket Install	Vertical installation
Product Size	L x W x H = 928 x 50 x 60mm
Mounting Length	889mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut
Output	
Socket Type	IEC C13 and IEC C19
Socket Unit	(12)C13 + (2)C19
Input	
Cable with Plug	Ceeform 16A
Cable Specification	3G*2.5mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	16A
Max. Current	16A
Max. Power	4000 watt
Protection Function	
3LSP	3Lights Surge Protector
Control Function	
AV6	<ul style="list-style-type: none"> . Monitor input voltage . Monitor power factor . Monitor frequency . Monitor total load power . Monitor total load current . Monitor energy consumption . Button reset energy
Add-In	
Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE
Warranty	
2 (two) Years	Repair or replace