

# TECHNICAL DATASHEET

**14 Holes PDU Mix. Socket  
(12) IEC C13 + (2) IEC C19  
With 3L Surge Protector + AV6 Meter  
Input Ceeform 32A**



3L Surge Protector



Input : Ceeform 32A



Output : (12) IEC C13  
(2) IEC C19



Cable : 3G\*4.0mm<sup>2</sup>\*3m



Max. Power : 8000 Watt

<b>Specification</b>	
Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B12C2-6-5
<b>Physical</b>	
Case	Aluminium alloy coated Black
Power Input	Bottom single input
Bracket Install	Vertical installation
Product Size	L x W x H = 928 x 50 x 60mm
Mounting Length	889mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw ( $\phi$ 6 x 16mm), 4pcs M6 float nut
<b>Output</b>	
Socket Type	IEC C13 and IEC C19
Socket Unit	(12)C13 + (2)C19
<b>Input</b>	
Cable with Plug	Ceeform 32A
Cable Specification	3G*4.0mm <sup>2</sup> *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	8000 watt
<b>Protection Function</b>	
3LSP	3Lights Surge Protector
<b>Control Function</b>	
AV6	<ul style="list-style-type: none"> <li>. Monitor input voltage</li> <li>. Monitor power factor</li> <li>. Monitor frequency</li> <li>. Monitor total load power</li> <li>. Monitor total load current</li> <li>. Monitor energy consumption</li> <li>. Button reset energy</li> </ul>
<b>Add-In</b>	
Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE
<b>Warranty</b>	
2 ( two ) Years	Repair or replace