

TECHNICAL DATASHEET

New IPDU Series
Intelligent PDU with SNMP
16 Sockets IEC C13
Input IEC C14, 10A

3L Surge Protector



Input : IEC C14, 10A



Output : (16) IEC C13



Cable : 3G*2.5mm²*3m



Max. Power : 2500 Watt

Specification

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B16-12-2

Physical

Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1028 x 50 x 60mm
Mounting Length	989mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut

Output

Socket Type	IEC C13
Socket Unit	16 x IEC C13
Max. Ouput Current	15A

Input

Cable with Plug	IEC C14, 10A
Cable Spesification	3G*2.5mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	10A
Max. Current	10A
Max. Power	2500 watt

Protection Function

3LSP	3Lights Surge Protector
------	-------------------------

Feature

New IPDU Meter	. Remote network management . Cascadae management . RS485 . SNMP V1, V2, V3 . Monitor input voltage . Monitor total load current . Monitor total load power	. Monitor energy consumption . Monitor power facktor . Monitor output options . Voltage threshold setting . Current threshold setting . TH Sensor (optional) . USB port
----------------	---	---

Add-In

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

Warranty

2 (two) Years	Repair or replace
-----------------	-------------------