

# TECHNICAL DATASHEET

**3 Phase SIPDU 32A**  
**Intelligent PDU with RS-485**  
**24 Sockets IEC C13**  
**Input Ceeform 3P+N+E, 32A**



Input :  
Ceeform 3P+N+E, 32A



Output : (24) IEC C13



Cable : 5G\*6.0mm<sup>2</sup>\*3m



Max. Power : 21 k.watt

<b>Specification</b>	
<b>Brand</b>	YURRO
<b>Product Name</b>	Power Distribution Unit
<b>Part Number</b>	Y-B24-11-5.3P
<b>Physical</b>	
Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1228 x 50 x 60mm
Mounting Length	1189mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw ( $\phi$ 6 x 16mm), 4pcs M6 float nut
<b>Output</b>	
Socket Type	IEC C13
Socket Unit	24 x IEC C13
Max. Ouput Current	15A
<b>Input</b>	
Cable with Plug	IEC60309 3P+N+E, 32A
Cable Spesification	5G*6.0mm <sup>2</sup> *3M
Rating Voltage	380 - 415VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	21 Kw
<b>Feature</b>	
SIPDU	RS-485 Monitor input voltage Monitor total load current Monitor energy consumption Monitor power factor Monitor output option Voltage threshold setting Current threshold setting
<b>Add-In</b>	
Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE
<b>Warranty</b>	
2 (two) Years	Repair or replace