


TECHNICAL DATASHEET

New IPDU Series
Intelligent PDU with SNMP
24 Sockets IEC C13
Input IEC C20, 16A



3L Surge Protector



Input : IEC C20, 16A



Output : (24) IEC C13



Cable : 3G*2.5mm²*3m



Max. Power : 4000 Watt

Specification

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B24-12-3

Physical

Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1328 x 50 x 60mm
Mounting Length	1289mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw (φ 6 x 16mm), 4pcs M6 float nut

Output

Socket Type	IEC C13
Socket Unit	24 x IEC C13
Max. Ouput Current	15A

Input

Cable with Plug	IEC C20, 16A
Cable Spesification	3G*2.5mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	16A
Max. Current	16A
Max. Power	4000 watt

Protection Function

3LSP	3Lights Surge Protector
------	-------------------------

Feature

New IPDU Meter	. Remote network management	. Monitor energy consumption
	. Cascadae management	. Monitor power factkor
	. RS485	. Monitor output options
	. SNMP V1, V2, V3	. Voltage threshold setting
	. Monitor input voltage	. Current threshold setting
	. Monitor total load current	. TH Sensor (optional)
	. Monitor total load power	. USB port

Add-In

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

Warranty

2 (two) Years	Repair or replace
-----------------	-------------------