

TECHNICAL DATASHEET

PDU 24 Sockets IEC C13
With 3L Surge Protector + AV6 Meter
Input IEC C14, 10A



3L Surge Protector



Input : IEC C14, 10A



Output : (24) IEC C13



Cable : 3G*2.5mm²*3m



Max. Power : 2500 Watt

Specification

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B24-6-2

Physical

Case	Aluminium alloy coated Black
Power Input	Bottom single input
Bracket Install	Vertical installation
Product Size	L x W x H = 1228 x 50 x 60mm
Mounting Length	1189mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut

Output

Socket Type	IEC C13
Socket Unit	24 x IEC C13
Max. Output Current	15A

Input

Cable with Plug	IEC C14, 10A
Cable Specification	3G*2.5mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	10A
Max. Current	10A
Max. Power	2500 watt

Protection Function

3LSP	3Lights Surge Protector
------	-------------------------

Control Function

AV6	. Monitor input voltage	. Monitor total load current
	. Monitor power factor	. Monitor energy consumption
	. Monitor frequency	. Button reset energy
	. Monitor total load power	

Add-In

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

Warranty

2 (two) Years	Repair or replace
-----------------	-------------------