


TECHNICAL DATASHEET

**36 Holes PDU Mix. Socket
(30) IEC C13 + (6) IEC C19
with 3L Surge Protector
Input Ceeform 32A**



Input : Ceeform 32A



Output : (30) IEC C13
(6) IEC C19



Cable : 3G*6.0mm²*3m



Max. Power : 8000 Watt

Specification	
Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B30C6-2-5
Physical	
Case	Aluminium alloy coated Black
Power Input	Bottom singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1578 x 50 x 60mm
Mounting Length	1539mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw (φ 6 x 16mm), 4pcs M6 float nut
Output	
Socket Type	IEC C13 and IEC C19
Socket Unit	(30)C13 + (6)C19
Input	
Cable with Plug	Ceeform, 32A
Cable Spesification	3G*6.0mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	8000 watt
Protection Function	
3LSP	3Lights Surge Protector
Add-In	
Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE
Warranty	
2 (two) Years	Repair or replace