

# TECHNICAL DATASHEET

**8 Holes PDU Mix. Socket  
(6) IEC C13 + (2) IEC C19  
with 3L Surge Protector  
Input Ceeform 32A**



Input : Ceeform, 32A



Output : (6) IEC C13  
: (2) IEC C19



Cable : 3G\*4.0 mm<sup>2</sup>\*3m



Max. Power : 8000 Watt



**Specification**

<b>Brand</b>	YURRO
<b>Product Name</b>	Power Distribution Unit
<b>Part Number</b>	Y-B6C2-2-5

**Physical**

Case	Aluminium alloy coated Black
Power Input	Left single input
Bracket Install	19inch Horizontal installation
Product Size	L x W x H = 482.6 x 44.5 x 62mm
Mounting Length	459.6 mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw ( $\phi$ 6 x 16mm), 4pcs M6 float nut

**Output**

Socket Type	IEC C13 and IEC C19
Socket Unit	(6)C13 + (2)C19

**Input**

Cable with Plug	Ceeform 32A
Cable Specification	3G*4.0mm <sup>2</sup> *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	8000 watt

**Protection Function**

3LSP	3Lights Surge Protector
------	-------------------------

**Add-In**

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

**Warranty**

2 ( two ) Years	Repair or replace
-----------------	-------------------