

# TECHNICAL DATASHEET

PDU 16 Sockets IEC C19  
with 3L Surge Protector + MCB  
Input Ceeform 16A



3L Surge Protector



Input : Ceeform 16A



Output : (16) IEC C19



Cable : 3G\*2.5mm<sup>2</sup>\*3m



Max. Power : 4000 Watt

**Specification**

<b>Brand</b>	<b>YURRO</b>
<b>Product Name</b>	<b>Power Distribution Unit</b>
<b>Part Number</b>	<b>Y-C16-3-4</b>

**Physical**

Case	Aluminium alloy coated Black
Power Input	Bottom single input
Bracket Install	Vertical installation
Product Size	L x W x H = 1328 x 50 x 60mm
Mounting Length	1289mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw ( $\phi$ 6 x 16mm), 4pcs M6 float nut

**Output**

Socket Type	IEC C19
Socket Unit	16 x IEC C19
Max. Output Current	16A

**Input**

Cable with Plug	Ceeform, 16A
Cable Specification	3G*2.5mm <sup>2</sup> *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	16A
Max. Current	16A
Max. Power	4000 watt

**Protection Function**

3LSP	3Lights Surge Protector
Circuit Breaker	1Pole 16A

**Add-In**

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

**Warranty**

2 (two) Years	Repair or replace
---------------	-------------------