


TECHNICAL DATASHEET

12 Holes PDU Universal Socket
With 3L Surge Protector + AV6 Meter
Input Ceeform 16A



3L Surge Protector



Input : Ceeform 16A



Output : (12) GB2099.3-1



Cable : 3G*2.5mm²*3m



Max. Power : 4000 Watt

Specification

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-E12-6-4

Physical

Case	Aluminium alloy coated Black
Power Input	Bottom singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1028 x 50 x 60mm
Mounting Length	989mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut

Output

Socket Type	GB2099.3-1
Socket Unit	12 x GB2099.3-1
Max. Ouput Current	10A

Input

Cable with Plug	Ceeform, 16A
Cable Spesification	3G*2.5mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	16A
Max. Current	16A
Max. Power	4000 watt

Protection Function

3LSP	3Lights Surge Protector
------	-------------------------

Control Function

AV6	. Monitor input voltage	. Monitor total load current
	. Monitor power factor	. Monitor energy consumption
	. Monitor frequency	. Button reset energy
	. Monitor total load power	

Add-In

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

Warranty

2 (two) Years	Repair or replace
-----------------	-------------------