

# TECHNICAL DATASHEET

## 6 Holes PDU Universal Socket with Circuit Breaker Input IEC C20, 16A



Input : IEC C20, 16A



Output : (6) GB2099.3-1



Cable : 3G\*1.5 mm<sup>2</sup>\*3m



Max.Power : 4000 Watt



| <b>Specification</b>       |   |
|----------------------------|---|
| <b>Brand</b>               | <b>YURRO</b>  |
| <b>Product Name</b>        | <b>Power Distribution Unit</b>                          |
| <b>Part Number</b>         | <b>Y-E6-3-3</b>   |
| <b>Physical</b>            |   |
| Case                       | Aluminium alloy coated Black                            |
| Power Input                | Left single input                                       |
| Bracket Install            | 19inch Horizontal installation                          |
| Product Size               | L x W x H = 482.6 x 44.5 x 62mm                         |
| Mounting Length            | 459.6 mm  |
| Mounting Style             | 2 ends Brackets   |
| Fittings                   | 4 pcs cross screw ( $\phi$ 6 x 16mm), 4pcs M6 float nut |
| <b>Output</b>              |   |
| Socket Type                | GB2099.3-1  |
| Socket Unit                | 6 x GB2099.3-1  |
| Max. Output Current        | 10A   |
| <b>Input</b>               |   |
| Cable with Plug            | IEC C20, 16A  |
| Cable Specification        | 3G*1.5mm <sup>2</sup> *3M                               |
| Rating Voltage             | 220 - 250VAC 50 - 60 Hz                                 |
| Rating Current             | 16A   |
| Max. Current               | 16A   |
| Max. Power                 | 4000 watt   |
| <b>Protection Function</b> |   |
| MCB                        | Circuit Breaker 16A                                     |
| <b>Control Function</b>    |   |
| LED                        | Power Indicator   |
| <b>Add-In</b>              |   |
| Interior Connection Wire   | Brass bar   |
| Interior Connection Style  | Soldering tin   |
| Fix the Cable              | PG Cable clamp  |
| Safety Authentication      | CE  |
| <b>Warranty</b>            |   |
| 2 ( two ) Year             | Repair or replace                                       |