

TECHNICAL DATASHEET

**7 Holes PDU Mix. Socket
(2)DIN49440 + (3)C13 + (2)C19
with AV6 Meter
Input IEC Ceeform 32A**



Input : Ceeform, 32A



**Output : (2) DIN49440
(3) IEC C13
(2) IEC C19**



Cable : 3G*4.0 mm²*3m



Max. Power : 8000 Watt



Specification	
Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-A2B3C2-6-5
Physical	
Case	Aluminium alloy coated Black
Power Input	Left single input
Bracket Install	19inch Horizontal installation
Product Size	L x W x H = 482.6 x 44.5 x 62mm
Mounting Length	459.6 mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw (φ 6 x 16mm), 4pcs M6 float nut
Output	
Socket Type	DIN49440 and IEC C13 and IEC C19
Socket Unit	(2) DIN49440 + (3) C13 + (2) C19
Input	
Cable with Plug	Ceeform 32A
Cable Spesification	3G*4.0mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	8000 watt
Control Function	
AV6	<ul style="list-style-type: none"> . Monitor input voltage . Monitor power factor . Monitor frequency . Monitor total load power . Monitor total load current . Monitor energy consumption . Button reset energy
Add-In	
Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE
Warranty	
2 (two) Years	Repair or replace