

# TECHNICAL DATASHEET

**7 Holes Mix. Socket  
(2) DIN49440 + (5) IEC C13  
with AV6 Meter  
Input Ceeform 32A**



**Input : Ceeform, 32A**



**Output : (2) DIN49440  
(5) IEC C13**



**Cable : 3G\*4.0 mm<sup>2</sup>\*3m**



**Max. Power : 8000 Watt**



**Specification**

<b>Brand</b>	<b>YURRO</b>
<b>Product Name</b>	<b>Power Distribution Unit</b>
<b>Part Number</b>	<b>Y-A2B5-6-5</b>

**Physical**

Case	Aluminium alloy coated Black
Power Input	Left single input
Bracket Install	19inch Horizontal installation
Product Size	L x W x H = 482.6 x 44.5 x 62mm
Mounting Length	459.6 mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw ( $\phi$ 6 x 16mm), 4pcs M6 float nut

**Output**

Socket Type	DIN49440 and IEC C13
Socket Unit	(2)DIN49440 + (5)C13

**Input**

Cable with Plug	Ceeform 32A
Cable Specification	3G*4.0mm <sup>2</sup> *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	8000 watt

**Control Function**

AV6	. Monitor input voltage	. Monitor total load current
	. Monitor power factor	. Monitor energy consumption
	. Monitor frequency	. Button reset energy
	. Monitor total load power	

**Add-In**

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

**Warranty**

2 ( two ) Years	Repair or replace
-----------------	-------------------