

TECHNICAL DATASHEET

**8 Holes PDU Mix. Socket
(2) DIN49440 + (6) IEC C13
with Surge Protector
Input IEC C14, 10A**



Input : IEC C14, 10A



Output : (2) DIN49440
: (6) IEC C13



Cable : 3G*1.5 mm²*3m



Max. Power : 2500 Watt



Specification	
Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-A2B6-1-2
Physical	
Case	Aluminium alloy coated Black
Power Input	Left single input
Bracket Install	19inch Horizontal installation
Product Size	L x W x H = 482.6 x 44.5 x 62mm
Mounting Length	459.6 mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut
Output	
Socket Type	DIN49440 and IEC C13
Socket Unit	(2)DIN49440 + (6)C13
Input	
Cable with Plug	IEC C14, 10
Cable Specification	3G*1.5mm ² *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	10A
Max. Current	10A
Max. Power	2500 watt
Protection Function	
SPD	Surge Protector Device
Add-In	
Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE
Warranty	
2 (two) Years	Repair or replace