

# TECHNICAL DATASHEET

12 Holes PDU Mix. Socket  
(6) DIN49440 + (6) GB2099.3-1  
With 3L Surge Protector + AV6 Meter  
Input Ceeform 32A



3L Surge Protector



Input : Ceeform 32A



Output : (6) DIN49440  
(6) GB2099.3-1



Cable : 3G\*4.0mm<sup>2</sup>\*3m



Max. Power : 8000 Watt

**Specification**

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-A6E6-6-5

**Physical**

Case	Aluminium alloy coated Black
Power Input	Bottom single input
Bracket Install	Vertical installation
Product Size	L x W x H = 1028 x 50 x 60mm
Mounting Length	989mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw ( φ 6 x 16mm), 4pcs M6 float nut

**Output**

Socket Type	DIN49440 and GB2099.3-1
Socket Unit	(6) DIN49440 + (6) GB2099.3-1

**Input**

Cable with Plug	Ceeform 32A
Cable Specification	3G*4.0mm <sup>2</sup> *3M
Rating Voltage	220 - 250VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	8000 watt

**Protection Function**

3LSP	3Lights Surge Protector		
------	-------------------------	--	--

**Control Function**

AV6	<ul style="list-style-type: none"> <li>. Monitor input voltage</li> <li>. Monitor power factor</li> <li>. Monitor frequency</li> <li>. Monitor total load power</li> <li>. Monitor total load current</li> <li>. Monitor energy consumption</li> <li>. Button reset energy</li> </ul>
-----	---

**Add-In**

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

**Warranty**

2 ( two ) Years	Repair or replace
-----------------	-------------------