

TECHNICAL DATASHEET

**3 Phase PDU 32A
24 Hole Mix. Socket
(21) IEC C13 + (3) IEC C19
with Power Indicator
Input Ceeform 3P+N+E, 32A**



Input :
Ceeform 3P+N+E, 32A



Output : (21) IEC C13
(3) IEC C19



Cable : 5G*6.0mm²*3m



Max. Power : 21 k.watt

Specification	
Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B21C3-0-5.3P
Physical	
Case	Aluminium alloy coated Black
Power Input	Bottom singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1228 x 50 x 60mm
Mounting Length	1189mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut
Output	
Socket Type	IEC C13 and IEC C19
Socket Unit	(21) IEC C13 + (3) IEC C19
Input	
Cable with Plug	IEC60309 3P+N+E, 32A
Cable Spesification	5G*6.0mm ² *3M
Rating Voltage	380 - 415VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	21 Kw
Control Function	
LED	3ea Power Indicator
Add-In	
Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE
Warranty	
2 (two) Years	Repair or replace