

TECHNICAL DATASHEET

3 Phase SIPDU 32A
Intelligent PDU with RS-485
30 Holes Mix. Socket
(24) IEC C13 + (6) IEC C19
Input Ceeform 3P+N+E, 32A



Input :
Ceeform 3P+N+E, 32A



Output : (24) IEC C13
(6) IEC C19



Cable : 5G*6.0mm²*3m



Max. Power : 21 k.watt

Specification

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-B24C6-11-5.3P

Physical

Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1578 x 50 x 60mm
Mounting Length	1539mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut

Output

Socket Type	IEC C13
Socket Unit	(24) IEC C13 + (6) IEC C19

Input

Cable with Plug	IEC60309 3P+N+E, 32A
Cable Spesification	5G*6.0mm ² *3M
Rating Voltage	380 - 415VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	21 Kw

Feature

SIPDU	RS-485
	Monitor input voltage
	Monitor total load current
	Monitor energy consumption
	Monitor power factor
	Monitor output option
	Voltage threshold setting
	Current threshold setting

Add-In

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

Warranty

2 (two) Years	Repair or replace
---------------	-------------------