

# TECHNICAL DATASHEET

3 Phase PDU 32A  
30 Holes Mix. Socket  
(24) IEC C13 + (6) IEC C19  
with Circuit Breaker  
Input Ceeform 3P+N+E, 32A



Input :  
Ceeform 3P+N+E, 32A



Output : (24) IEC C13  
(6) IEC C19



Cable : 5G\*6.0mm<sup>2</sup>\*3m



Max. Power : 21 k.watt

<b>Specification</b>	
<b>Brand</b>	YURRO
<b>Product Name</b>	Power Distribution Unit
<b>Part Number</b>	Y-B24C6-3-5.3P
<b>Physical</b>	
Case	Aluminium alloy coated Black
Power Input	Bottom singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 1728 x 50 x 60mm
Mounting Length	1689mm
Mounting Style	2 ends Brackets
Fittings	4 pcs cross screw ( φ 6 x 16mm), 4pcs M6 float nut
<b>Output</b>	
Socket Type	IEC C13 and IEC C19
Socket Unit	(24) IEC C13 + (6) IEC C19
<b>Input</b>	
Cable with Plug	IEC60309 3P+N+E, 32A
Cable Spesification	5G*6.0mm <sup>2</sup> *3M
Rating Voltage	380 - 415VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	21 Kw
<b>Protection Function</b>	
MCB + LED	3ea Circuit Breaker + 3ea Power Indicator
<b>Add-In</b>	
Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE
<b>Warranty</b>	
2 (two) Years	Repair or replace