


TECHNICAL DATASHEET

3 Phase PDU 32A
12 Sockets IEC C19
With Ammeter Y-Series
Input Ceeform 3P+N+E, 32A



Max. Power : 21 Kw



Cable : 5G*6.0mm²*5m



Output : (12) IEC C19



Input :
Ceeform 3P+N+E, 32A

Specification

Brand	YURRO
Product Name	Power Distribution Unit
Part Number	Y-C12-7-5.3P

Physical

Case	Aluminium alloy coated Black
Power Input	Top singel input
Bracket Install	Vertical installation
Product Size	L x W x H = 928 x 50 x 60mm
Mounting Length	889mm
Mounting Style	2 ends Brakets
Fittings	4 pcs cross screw (ϕ 6 x 16mm), 4pcs M6 float nut

Output

Socket Type	IEC C19
Socket Unit	12 x IEC C19
Max. Output Current	16A

Input

Cable with Plug	IEC60309 3P+N+E, 32A
Cable Spesification	5G*6.0mm ² *5M
Rating Voltage	380 - 415VAC 50 - 60 Hz
Rating Current	32A
Max. Current	32A
Max. Power	21 Kw

Control Function

LED	3ea Power Indicator
Ammeter Y-Series	Monitor Volt (V) Monitor Ampere (A) Monitor Energy Consumption (Kwh) Monitor Power Factor

Add-In

Interior Connection Wire	Brass bar
Interior Connection Style	Soldering tin
Fix the Cable	PG Cable clamp
Safety Authentication	CE

Warranty

2 (two) Years	Repair or replace
---------------	-------------------